

# **PRODUCT DATA SHEET**

## PHOS COPPER ANODES NUGGETS

#### QUALITY SYSTEM CERTIFIED TO ISO 9001:2015

PRODUCT SPECIFICATION
IMC 352 - PHOS COPPER
C12220
C12220

Copper <sup>(1)</sup>	99.95 MIN%
Iron	0.003 MAX%
Sulfur	0.003 MAX%
Lead	0.002 MAX%
Antimony	0.002 MAX%
Nickel	0.002 MAX%
Arsenic	0.001 MAX%
Tin	0.002 MAX%
Total Other <sup>(2)</sup>	0.010 MAX%
Phosphorus	0.040 - 0.065 %

#### (1) Copper includes Silver and Phosphorus

(2) Other metallic elements include: Bi, Cd, Mn, Hg, Se, Te, Zn



#### SIZES

#### **PHOS COPPER NUGGETS**

.56" x .5" / 14mm x 12.5mm .56" x .75" / 14mm x 19mm .56" x 1" / 14mm x 25mm .75" x .5" / 19mm x 12.5mm .75" x .75" / 19mm x 19mm .75" x 1" / 19mm x 25mm 1" x 1" / 25mm x 25mm 1.375" x 1" / 35mm x 25mm 1.375" x 1.5" / 35mm x 38mm

### PACKAGING

- 44 lb Boxes / 20 Kg
  2200 lb Pallets / 1000 Kg
- 220 lb Drums / 100 Kg 1980 lb Pallets / 900 Kg
- Bulk Packaging Available

#### FEATURES

- Hot rolling produces a fine-grained structure.
- Uniform Phos distribution reduces sludging.
- Consistent dissolution.
- Special process eliminates precleaning.
- For use in any anode basket or tray.
- Color-coded, user-friendly packaging.
- Certificate of Analysis issued for every lot.

#### TYPICAL APPLICATIONS

- Printed Circuits
- Plated on Plastic Trim
- Decorative Plating
- Electronic Components
- Corrosion Protection in Automotive Parts
- Electrical Connectors
- Power Distribution Equipment
- Ammunition
- Coinage
- Rotogravure Cylinders
- Automotive Wheel Plating

This information herein is believed to be reliable, however, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable to damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patents.

> 135 Old Boiling Springs Road • Shelby, NC 28152 Phone: 704.482.8200 • Fax: 704.482.8038 www.imc-ma.com sales@imc-ma.com