



PRODUCT DATA SHEET

EXTRUDED DEPOLARIZED NICKEL ANODE BARS

QUALITY SYSTEM CERTIFIED TO ISO 9001:2015

PRODUCT SPECIFICATION

IMC 750 - EXTRUDED DEPOLARIZED NICKEL



Nickel & Cobalt	99.00 MIN%
Iron	0.30 MAX%
Copper	0.25 MAX%
Zinc	0.01 MAX%
Sulfur	0.005 - 0.012%
Nickel Oxide	0.10 - 1.25%

SIZES	PACKAGING
-------	-----------

DEPOLARIZED NICKEL BARS

- Boxed, Palletized

ELLIPTICAL BARS

- Pallet weight varies based on anode length

1.25" x 3.185" / 32mm x 81mm

DRILL AND TAP (D&T)

STD - 3/8-16 x 1"

Custom D&T Available

FEATURES

- Even dissolution as a result of very fine grain structure.
- For use with anode hooks or trays.
- Superior control of anode to cathode ratio.
- Certificate of Analysis issued for every lot.

TYPICAL APPLICATIONS

- Decorative Plating
- Electronic Components
- Electrical Connectors
- Wire Plating
- Aerospace Plating

This information herein is believed to be reliable, however, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable to damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patents.

135 Old Boiling Springs Road • Shelby, NC 28152

Phone: 704.482.8200 • Fax: 704.482.8038

www.imc-ma.com

sales@imc-ma.com