

PRODUCT DATA SHEET

ZINC ANODES

QUALITY SYSTEM CERTIFIED TO ISO 9001:2015

PRODUCT SPECIFICATION IMC 620 - LME SHG ZINC ASTM B6-6

Zinc	99.99 MIN%
Lead	0.003 MAX%
Cadmium	0.003 MAX%
Iron	0.002 MAX%
Tin	0.001 MAX%
Aluminum	0.001 MAX%
Copper	0.001 MAX%



SIZES (diameter)

ZINC BALLS & BARS 50mm / 2" (Balls) Custom Bars Available



PACKAGING

BALLS

 50 lb Boxes / 22.7 Kg 1800 lb Skids / 817 Kg

BARS

- Palletized
- Pallet weight varies based on anode length

FEATURES

- Flash-free anodes for ease of handling.
- Consistent dissolution rate.
- Consistent surface area.
- Quick-settling chacteristics avoid bridging, voids and basket damage (Balls).
- For use with anode hooks or trays (Bars).
- Certificate of Analysis issued for every lot.

TYPICAL APPLICATIONS

- Wire Plating
- Corrosion Protection in Automotive Parts
- Decorative Plating
- Electrical Enclosures
- Fasteners
- Coinage

This information herein is believed to be reliable, however, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable to damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patents.

> 135 Old Boiling Springs Road • Shelby, NC 28152 Phone: 704.482.8200 • Fax: 704.482.8038 www.imc-ma.com sales@imc-ma.com